RG products

Model name	Use ^{*1} /Storage ^{*2}	Incorrect indication	Correct indication
		Dimensions (without stand)	Dimensions (without stand)
MZ7/9 series	When in use	1605mm(W)×725mm(D)×730mm(H)	1625mm(W)×735mm(D)×740mm(H)
		(63 3/16"(W)×28 9/16"(D)×28 3/4"(H))	(63 31/32"(W)×28 15/16"(D)×29 1/8"(H))
	When in storage	1010mm(W)×725mm(D)×730mm(H)	1005mm(W)×735mm(D)×740mm(H)
		(39 3/4"(W)×28 9/16"(D)×28 3/4"(H))	(39 9/16"(W)×28 15/16"(D)×29 1/8"(H))
RZ9 series (with front loading tray)	When in use	1405mm(W)×700mm(D)×1080mm(H)	1415mm(W)×705mm(D)×1090mm(H)
			(55 23/32"(W)×27 3/4"(D)×42 29/32"(H))
	When is storage	775mm(W)×700mm(D)×1080mm(H)	780mm(W)×705mm(D)×1090mm(H)
			(30 23/32"(W)×27 3/4"(D)×42 29/32"(H))
RZ9 series	When in use	1405mm(W)×700mm(D)×660mm(H)	1415mm(W)×705mm(D)×665mm(H)
			(55 23/32"(W)×27 3/4"(D)×26 3/16"(H))
(without front loading tray)	When is storage	775mm(W)×700mm(D)×660mm(H)	780mm(W)×705mm(D)×665mm(H)
	When is storage		(30 23/32"(W)×27 3/4"(D)×26 3/16"(H))
	When in use	1380mm(W)×645mm(D)×660mm(H)	1415mm(W)×655mm(D)×665mm(H)
EZ5 series	When in use	(54 5/16"(W)×25 3/8"(D)×26"(H))	(55 23/32"(W)×25 25/32"(D)×26 3/16"(H))
	When in storage	785mm(W)×645mm(D)×660mm(H)	780mm(W)×655mm(D)×665mm(H)
		(30 17/32"(W)×25 3/8"(D)×26"(H))	(30 23/32"(W)×25 25/32"(D)×26 3/16"(H))
	When in use	1380mm(W)×645mm(D)×660mm(H)	1415mm(W)×655mm(D)×665mm(H)
EZ2/3 series		(54 5/16"(W)×25 3/8"(D)×26"(H))	(55 23/32"(W)×25 25/32"(D)×26 3/16"(H))
LZZ/3 series	When in storage	775mm(W)×645mm(D)×660mm(H)	780mm(W)×655mm(D)×665mm(H)
		(30 17/32"(W)×25 3/8"(D)×26"(H))	(30 23/32"(W)×25 25/32"(D)×26 3/16"(H))
	When in use	1270mm(W)×645mm(D)×510mm(H)	1280mm(W)×655mm(D)×515mm(H)
CZ180			(50 13/32"(W)×25 25/32"(D)×20 9/32"(H))
	When in storage	650mm(W)×645mm(D)×500mm(H)	660mm(W)×655mm(D)×505mm(H)
			(26"(W)×25 25/32"(D)×19 7/8"(H))
CZ100	When in use	1270mm(W)×645mm(D)×510mm(H)	1280mm(W)×655mm(D)×515mm(H)
			(50 13/32"(W)×25 25/32"(D)×20 9/32"(H))
	When in storage	655mm(W)×645mm(D)×500mm(H)	660mm(W)×655mm(D)×505mm(H)
			(26"(W)×25 25/32"(D)×19 7/8"(H))
KS800	-	1200mm(W)×600mm(D)×550mm(H)	1250mm(W)×605mm(D)×550mm(H)
			(49 3/16"(W)×23 13/16"(D)×21 5/8"(H))

IJ products

Model name	Use*1/Storage*2	Incorrect indication Dimensions	Weight	Correct indication Dimensions	Weight
			weight		weight
HC5500 with RISO Auto-control Stacking Tray II	When in use	1800mm(W)×695mm(D)×1135mm(H)	Approx. 266kg	1800mm(W)×705mm(D)×1145mm(H)	Approx. 263kg
	When is storage	1220mm(W)×695mm(D)×1135mm(H)	Арргох. 266кд	1220mm(W)×705mm(D)×1145mm(H)	
RISO Scanner HS2000	-	642mm(W)×551mm(D)×247.5mm(H)	Approx. 27kg	650mm(W)×560mm(D)×255mm(H)	No change
HC Finisher	-	1358mm(W)×725mm(D)×1165mm(H)	Approx. 143kg	1360mm(W)×730mm(D)×1175mm(H)	No change
ComColorExpress IS700C	-	180mm(W)×405mm(D)×359mm(H)	Approx. 10kg	185mm(W)×415mm(D)×360mm(H)	No change
ComColor 9050/7050/3050 Main Unit	When in use	1210mm(W)×695mm(D)×1020mm(H) (47 5/8"(W)×27 3/8"(D)×40 3/16"(H))	Approx. 180kg (397lb)	1220mm(W)×705mm(D)×1030mm(H) (48 1/32"(W)×27 3/4"(D)×40 9/16"(H))	Approx. 168kg (371lb)
	When in storage	1150mm(W)×695mm(D)×990mm(H) (45 1/4"(W)×27 3/8"(D)×39"(H))		1155mm(W)×705mm(D)×995mm(H) (45 15/32"(W)×27 3/4"(D)×39 3/16"(H))	
	Required Space	1210mm(W)×1230mm(D)×1020mm(H)		1220mm(W)×1240mm(D)×1030mm(H)	
	*Feed trays opened	(47 5/8"(W)×48 7/16"(D)×40 3/16"(H))		(48 1/32"(W)×48 13/16"(D)×40 9/16"(H))	
ComColor 7010/3010 Main Unit	When in use	1210mm(W)×695mm(D)×1020mm(H) (47 5/8"(W)×27 3/8"(D)×40 3/16"(H))	(353lb)	1220mm(W)×705mm(D)×1030mm(H) (48 1/32"(W)×27 3/4"(D)×40 9/16"(H))	Approx. 146kg (322lb)
	When in storage	1150mm(W)×695mm(D)×990mm(H)		1155mm(W)×705mm(D)×995mm(H)	
	-	(45 1/4"(W)×27 3/8"(D)×39"(H))		(45 15/32"(W)×27 3/4"(D)×39 3/16"(H))	
	Required Space	1210mm(W)×1230mm(D)×1020mm(H)		1220mm(W)×1240mm(D)×1030mm(H)	
	*Feed trays opened	(47 5/8"(W)×48 7/16"(D)×40 3/16"(H))		(48 1/32"(W)×48 13/16"(D)×40 9/16"(H))	
Scanner HS4000	-	642mm(W)×551mm(D)×248mm(H)	Approx. 28kg	650mm(W)×560mm(D)×255mm(H)	No change
		(25 1/4"(W)×21 11/16"(D)×9 3/4"(H))	(62lb)	(25 9/16"(W)×22 1/16"(D)×10 1/32"(H))	nto ondingo
ComColor Main Unit with Scanner HS4000 and Stand HS4000	When in use	1220mm(W)×800mm(D)×1220mm(H)		1225mm(W)×810mm(D)×1220mm(H)	
	Required Space	(48"(W)×31 1/2"(D)×48"(H))	_	(48 7/32"(W)×31 7/8"(D)×48 1/32"(H))	
	*Feed trays and	1220mm(W)×1335mm(D)×1610mm(H)	-	- 1225mm(W)×1345mm(D)×1615mm(H)	
	Scanner cover opened	(48"(W)×52 9/16"(D)×63 3/8"(H))		(48 7/32"(W)×52 31/32"(D)×63 19/32"(H))	
ComColor Main Unit with Face Down Offset Tray		1240mm(W)×695mm(D)×1105mm(H)		1205mm(W)×705mm(D)×1110mm(H)	
	When in use	(48 13/16"(W)×27 3/8"(D)×43 1/2"(H))		(47 7/16"(W)×27 3/4"(D)×43 11/16"(H))	
	When in store to	1200mm(W)×695mm(D)×1105mm(H)	-	Sama an above when in storage	
-	When in storage	(47 1/4"(W)×27 3/8"(D)×43 1/2"(H))		Same as above when in storage.	
ComColor Main Unit	When in use	1710mm(W)×695mm(D)×1020mm(H)		1705mm(W)×705mm(D)×1030mm(H)	
with RISO Auto-control Stacking Tray II	When in use	(67 5/16"(W)×27 3/8"(D)×40 3/16"(H))	-	(67 1/8"(W)×27 3/4"(D)×40 9/16"(H))	
	When in storage	1335mm(W)×695mm(D)×990mm(H)		1340mm(W)×705mm(D)×1045mm(H)	
	When in storage	(52 9/16"(W)×27 3/8"(D)×39"(H))		(52 3/4"(W)×27 3/4"(D)×41 5/32"(H))	
	When in use	1830mm(W)×695mm(D)×1020mm(H)		1845mm(W)×705mm(D)×1030mm(H)	
ComColor Main Unit		(72"(W)×27 3/8"(D)×40 3/16"(H))	-	(72 21/32"(W)×27 3/4"(D)×40 9/16"(H))	
with Wide Stacking Tray	When in storage	1770mm(W)×695mm(D)×990mm(H)		1785mm(W)×705mm(D)×995mm(H)	
ComColor Main Unit	Ű	(69 11/16"(W)×27 3/8"(D)×39"(H))		(70 9/32"(W)×27 3/4"(D)×39 3/16"(H))	
with Face Down Offset Tray and	When in use	1740mm(W)×695mm(D)×1105mm(H)	_	1695mm(W)×705mm(D)×1110mm(H)	-
RISO Auto-control Stacking Tray II		(68 1/2"(W)×27 3/8"(D)×43 1/2"(H))	-	(66 23/32"(W)×27 3/4"(D)×43 11/16"(H))	
ComColor Main Unit					
with Face Down Offset Tray and	When in use	1860mm(W)×695mm(D)×1105mm(H)	-	1840mm(W)×705mm(D)×1110mm(H)	-
Wide Stacking Tray		(73 1/4"(W)×27 3/8"(D)×43 1/2"(H))		(72 7/16"(W)×27 3/4"(D)×43 11/16"(H))	
Multifunction Finisher		1100mm(W)×760mm(D)×1165mm(H)	Approx. 131kg	1120mm(W)×765mm(D)×1130mm(H)	No change
Multiful cuori i misnei	-	(43 5/16"(W)×29 15/16"(D)×45 7/8"(H))	(289lb)	(44 3/32"(W)×30 1/8"(D)×44 1/2"(H))	No change
ComColor Main Unit with Multifunction Finisher	When in use	2295mm(W)×760mm(D)×1165mm(H)		2315mm(W)×765mm(D)×1130mm(H)	
		(90 3/8"(W)×29 15/16"(D)×45 7/8"(H))	_	(91 5/32"(W)×30 1/8"(D)×44 1/2"(H))	
	When in storage	2235mm(W)×760mm(D)×1165mm(H)	-	Same as above when in storage.	_
	when in storage	(88"(W)×29 15/16"(D)×45 7/8"(H))	_	e e e e e e e e e e e e e e e e e e e	
	Required Space	2295mm(W)×1275mm(D)×1165mm(H)		2315mm(W)×1280mm(D)×1130mm(H)	
		(90 3/8"(W)×50 3/16"(D)×45 7/8"(H))	1	(91 5/32"(W)×50 13/32"(D)×44 1/2"(H))	
ComColorExpress IS900C	-	180mm(W)×405mm(D)×356mm(H)	Approx. 10kg	185mm(W)×415mm(D)×360mm(H)	No change
		(7 1/16"(W)×15 15/16"(D)×14"(H))	(22lb)	(7 9/32"(W)×16 11/32"(D)×14 3/16"(H))	

*1 Standard feed tray and Ejection tray are open. Other covers and trays are closed. *2 All covers and trays are closed.